

	REV	REVISIONS REV. DESCRIPTION BY DATE			
COALESCING VENT OIL LEVEL OIL DRAIN .14 J	12.68	■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■	AG	5.73 0 0 0 0 0 0 0 0 0 0 0 0 0	4 BOX
Ø 1.625 SHAFT W/STD 3/8" SQ x 2.25" KEY 1/2-13 UNC T .75 (4) PLS. EQ. SP. ON A Ø 8.46 B.C.					
		AG DIMENSION			
		OUTPUT RPM RANG	E 5 HP	7.5 HP	10 HP
		71-200			28.04
		51-70		29.45	
7.29		36-50	26.85	STAINLE	
		UNLESS OTHERWISE SPECIFIED	17-4 H1150 SHAFT		
2. OTHER RATIOS AVAILABLE UPON REQUEST THE REP WHOLE O WHOLE O WRITTEN	WWING CONTAINS INFORMATION WHICH IS TARY AND CONFIDENTIAL TO STAINLESS I, INC., AND IS TRANSMITTED IN CONFIDENCE, RODUCTION, USE OR DISCLOSURE, IN DR IN PART, OF THE DESIGN CONTAINED TO OTHERS IS PROHIBITED WITHOUT THE I CONSENT OF STAINLESS MOTORS, INC.	DEBURR AND BREAK ALL SHARP EDGES 0.005 - 0.015	#4 LINE GENERAL TOLERANCES: XX = +/-0.015 XX = +/-0.005 XX = +/-0.005 ANGULAR = +/-1/2 ⁶	DRAWN: BDJ CHECK:	SBT1200 SOLID SHAFT C-FACE MOUNT
NOTES:	IGHT STAINLESS MOTORS, INC. ALL RIGHTS D. YEAR OF COPYRIGHT IS FIRST YEAR D ON THE DRAWING.	LL RIGHTS REFERENCE DRAWING: DRAWING: DRAWING F:\Website\GEARBOXES\SBT\SBT1200SXXXCXXX NUMBER:			